



## 1. Introduction

This 4K60 HDMI over Fiber Extender can extend HDMI signal up to 300m/ 984ft over an OM4 multimode single optical fiber cable. The resolution is up to 4K60 4:4:4. It supports HDMI HDP/DDC/CEC/ARC transmission. The transmitter features one HDMI input, one LC fiber optical output and one Micro USB power supply port (transmitter also can be powered by the connected HDMI source device). The receiver features one HDMI output, one LC fiber optical input and one Micro USB power supply port. This product has the advantages of strong anti-interference, high safety performance, small size and light weight, and has incomparable advantages in long-distance transmission.

## 2. Features

- HDCP 2.2 compliant
- Support 18Gbps video bandwidth
- Support video resolution up to 4K60 4:4:4, as specified in HDMI 2.0b
- Signal transmission distance can be extended up to 300m/984ft over an OM4 multimode single optical fiber cable
- Support HDMI HDP/DDC/CEC/ARC transmission
- HDMI Audio formats support LPCM, Dolby Digital/Plus/EX, Dolby True
- HD, Dolby Atmos, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD
- Support HDR, HDR10, HDR10+, Dolby Vision, HLG pass-through
- Fiber module included (Embedded)
- Standard single Fiber LC connector
- Micro USB power supply
- 2x USB cables and 2x 15cm HDMI female to male cables included
- Compact design for easy and flexible installation

## 3. Package Contents

- 1 × 4K60 HDMI over Fiber Extender (Transmitter)
- 1 × 4K60 HDMI over Fiber Extender (Receiver)
- 2 × HDMI Adapter Cable (male to female, 15cm)
- 2 × USB Cable (USB A to Micro USB, 1m, shielded)
- 1 × User Manual

## 4. Specifications

Technical	
HDMI Compliance	HDMI 2.0b
HDCP Compliance	HDCP 2.2
Video Bandwidth	18Gbps
Audio Latency	No latency
Video Latency	No latency
Video Resolution	Up to 4K60 4:4:4
Color Space	RGB, YCbCr 4:4:4 / 4:2:2 / 4:2:0
Color Depth	8/10/12bit
HDR	HDR, HDR10, HDR10+, Dolby Vision, HLG
HDMI Audio Formats	LPCM, Dolby Digital/Plus/EX, Dolby True HD, Dolby Atmos, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD
Transmission Distance	300m/984ft (over an OM4 multimode single optical fiber cable)
Cable Specification	850nm 50/125um OM4 LC-LC multimode optical fiber cable (single fiber)
ESD Protection	IEC 61000-4-2: ±8kV (Air-gap discharge) & ±4kV (Contact discharge)
Connection	
Transmitter	Input: 1x HDMI IN [Type A, 19-pin male] 1x POWER [Micro USB, 5-pin female] Output: 1x FIBER OUT [LC, 1-pin female]
Receiver	Input: 1x FIBER IN [LC, 1-pin female] 1x POWER [Micro USB, 5-pin female] Output: 1x HDMI OUT [Type A, 19-pin male]
Mechanical	
Housing	Aluminum Enclosure
Color	Grey
Dimensions	Transmitter / Receiver: 45.5mm [W] x 20.5mm [D] x 17.5 mm [H]
Weight	Transmitter: 22g, Receiver: 22g
Power Supply	Transmitter: 5V USB power supply or HDMI signal source power supply Receiver: 5V USB power supply
Power Consumption	Transmitter: 0.9W (Max) Receiver: 0.2W (Max)
Operating Temperature	32 - 104°F / 0 - 40°C
Storage Temperature	-4 - 140°F / -20 - 60°C
Relative Humidity	20 - 90% RH (no condensation)